




■ VRLA Battery- High Temperature Series

ZOWIE15S(48V200Ah)

- Intra-system balancing
- Flame retardant system to UL94V-0
- Good high temperature performance
- High cycle times and long service life
- Safe Lithium Iron Phosphate Technology
- Thousands of cycles, under normal conditions
- High energy density and conversion efficiency
- Environmental Friendly, without any heavy metals
- Complete with Battery Management System built-in
- Can use most standard VRLA chargers for this system
- Low self discharge rate of 2 years before required recharging
- Easy installation, can be in 19-inch standard cabinet or be wall-mounted
- Built-in automatic protection for over-charge, over-discharge & over-temperature conditions



Dimensions-mm









Characteristic

Item	Specification						
Model	ZOWIE15S48V200AH						
Rated Capacity (5HR)	200 Ah						
Nominal Voltage	48 V						
Discharge Ending Voltage	40 V						
Charging Limited Voltage	54.75V						
Max. Charging Current	150 A						
Max. Continue Discharging Current	150 A						
Weight	Approx. 80Kg						
Display	With display screen/Optional						
Protocol	CANBUS/ MODBUS						
Parallel Connection	Parallel connection is optional (up to 15P).						
Dimensions (W*D*H) mm (inches)	442 (17.40") * 550 (21.65") * 244 (9.61") customizable						
Cell	3.2V 200Ah						
Design life	More than 20 years						
Cycle Life	More than 3500 cycles at 100% DOD.						
IP Class	lp31						
Outer Package Material	Black bake lacquer steel case (battery rack or cabinet is optional)						
Operating Temperature	Charging: 0 to +60°C Discharging: -20 to +60°C Storage: -20 to +60°C						

Discharge Table

Constant Current Discharge Table (Amperes) at 25℃									
Model	Voltage Time	75 min	2 h	3 h	5 h	10 h			
LFeLi-48200MB16	End of discharge voltage 43.2 V	150A	98 A	66 A	40 A	20 A			

Constant Power Discharge Table (Watts) at 25 [°] ℃								
Model	Voltage Time	75 min	2 h	3 h	5 h	10 h		
LFeLi-48200MB16	End of discharge voltage 43.2 V	7600W	4990W	3398W	2016 W	1017W		

Publication No :ZOWIE-48200MB16-PD-EN-V2.3-202204

